

*Sub 1*  
~~(software managing setup and execution of IP calls between call~~  
 appliances through the routers;

wherein IP calls are managed between one of said call appliances  
 originating IP calls, wherein the IP calls terminate to an end destination of  
 another of said call appliances by the software by setting up separate and distinct  
 end node legs between call appliances and routers, and separate and distinct  
 intermediate legs between routers, and then joining and disjoining legs to  
 establish voice communication and to provide telephony functions between said  
 call appliances

2. (Unchanged) The system of claim 1 wherein call appliances include  
 Interactive Voice Response(IVR) units, and wherein the system establishes end-  
 node legs between IVRs and IP routers.

3. (Unchanged) The system of claim 1 wherein, in providing telephony  
 functions, call legs once established and joined may be disjoined and maintained  
 in established state for future use to be rejoined to other established call legs.

4. (Unchanged) The system of claim 1 wherein the software executes directly on  
 one or more IP routers connected to the network.

5. (Unchanged) The system of claim 1 wherein the software executes on one or  
 more processors enhancing IP routers on the network.

6. (Unchanged) The system of claim 1 further comprising a local area network  
 (LAN) connecting end appliances at one or more of the IP routers, and wherein  
 end-node legs are established via the LAN to appliances on the LAN.

*Sub 2*  
 7. (Twice Amended) A method for simulating connection-oriented telephony  
 functions in an IP network, comprising steps of:

(a) managing IP calls by interconnecting two or more IP routers with two or more Internet capable call appliances on a network, at least one of said call appliances originating the IP calls, and terminating IP calls to destinations at another of said call appliances ;

(b) setting up separate and distinct end-node call legs between the call appliances and routers, and separate and distinct intermediate call legs between routers; and

(c) joining and disjoining legs to provide telephony functions between said call appliances.

8. (Unchanged) The method of claim 7 wherein call appliances include Interactive Voice Response(IVR) units, and wherein the system establishes end-node legs between IVRs and IP routers.

9. (Unchanged) The method of claim 7 comprising steps for disjoining call legs of completed calls and maintaining one or more disjoined legs in established state for future use to be rejoined to other established call legs in providing telephony functions.

10. (Unchanged) The method of claim 7 wherein the software executes directly on one or more IP routers connected to the network.

11. (Unchanged) The method of claim 7 wherein the software executes on one or more processors enhancing IP routers on the network.

12.(Unchanged) The method of claim 7 further comprising a local area network (LAN) connecting end appliances at one or more of the IP routers, and a step for establishing end-node legs via the LAN to appliances on the LAN.

Sub E3 13. (Once Amended) A method for establishing an IP telephone call from a first IP-capable appliance through first and second IP routers to a second IP-capable appliance, comprising steps of:

(a) setting up a separate and distinct end-node call leg between the first appliance originating an IP call and the first router;

b3 (b) setting up a separate and distinct end-node call leg between the second appliance receiving and being the destination for the IP call, and the second router;

(c) setting up at least one separate and distinct intermediate call leg between the first and second IP routers; and

(d) joining the call legs to establish voice communication between said first and second appliances.

14. (Once Amended) The method of claim 13 further comprising additional interconnected routers and appliances, and including steps for setting up further call legs to additional appliances and between routers, and for joining and disjoining call legs to establish the voice communication by different paths over established call legs.

15. (Unchanged) The method of claim 14 wherein some call legs are maintained after being disjoined from active calls to be used later to be joined to other call legs to create other active calls.

16. (Unchanged) The method of claim 14 further comprising Interactive Voice Response (IVR) units, and wherein call legs are established to IVRs.

Sub E3 C2 17. (Twice Amended) A system for ~~simulating connection-oriented telephony~~ functions in an IP network, comprising:  
two or more IP routers interconnected with two or more Internet capable call appliances on a network; and

*Sub*  
*CD*  
~~software managing setup and execution of IP calls between call~~  
appliances through the routers;

wherein IP calls are managed by the software by setting up call legs between call appliances and routers, and between routers, which can then be manipulated, disjoined and joined to establish voice communication and to provide telephony functions between call appliances wherein one of said call appliances is the originator of the IP calls and another of said call appliances is the end destination of the IP calls.

---